

## FUEL SOURCE CO DATA

50/30

SAMPLE NO.	F. S. DESCRIPTION	CO (mg)	Pressure Drop
413	3x2, side flaps (dry)	32.07	
414	3 ribs/wide 1.020" flaps 1.012 web	30.82	
415	= (3 flaps)	33.48	
416	3 ribs/.030" flaps/.020" / 1 flaps	25.74	
417	2 flaps	30.84	
418	3 flaps	29.80	
419	4 ribs + 4 flaps	34.8	
420		34.2	
421		34.4	
422	3 ribs/.030" / .025" flaps / 3 flaps	31.	33
423	2	29.6	26
424	1	26.14	38
425	3 ribs/.030" / .0225" flaps / 2 flaps	31.74	44
426	1 flaps	25.22	46
427	multi-shallow grooves 1	25.97	39
428	1	24.29	39
429	1	27.22	43
430	multi-shallow grooves 2	21.68	55
431	(shallower) 2	22.19	63
432	2	26.59	44

# FUEL SOURCE CO DATA

SAMPLE NO.	F.S. DESCRIPTION	CO (Mg)	Pressure Drop.	Wt.
400	3 ribs, extruded 1222A (dry)	27.34	40	.140
401	=	24.	56	
402	=	20.85	59	
403	7 ribs, 7104J (dry)	58.65	44	.125
404	=	54.96	42	
405	=	55.65	46	
406	4 ribs. extruded, 1225A (dry)	22.87	45	.123
407		24.80	44	
408		23.19	43	